

Flat Panel Monitor



MODEL T15FP

15" Industrial LCD Openframe Display – VESA Standard Signals

Features

- 12Vdc or 115/230Vac Power Inputs
- Touchscreens - Easily integrated
- High Brightness & Long Life TFT Panel
- Resolution (1024 x 768 pixels)
- Metal Cased Construction
- Console/Rack Mounting – 1 U Rack (21mm)



Specifications

- **Type:** A-Si Color TFT
- **Colors:** 16.2 M
- **Resolution:** 1024 x 768 pixels (native)
- **Active Area:** 305 x 228 mm
- **Backlight Life:** 50,000 hours typical
- **Brightness:** 400 cd/m2 typical (nits)
- **Contrast Ratio:** 700:1
- **Viewing Angles:** 75/60/75/75
- **Response Time:** 8 msec (tr + tf)
- **Video Connections:** Analog RGB & TTL (optional)
- **Input Connectors:** 15-pin HD, 9 Pin (optional)
- **Sync. Type/Level:** Separate H&V (+/-ve) TTL
- **Horizontal Scan:** VESA Signals
- **Vertical Scan:** 45-100Hz
- **AC Model:** 115/230V 50/60Hz
External AC/DC Power Pack
- **Power Consumption:** 42 W (max)
- **Dimensions:** 330 x 255 x 20 mm (approx)
- **Weight:** 4 Kg (approx)
- **Housing:** Zinc-plated steel
- **Operating Temp:** 0 to 50 °C (32 to 122°F)
- **Storage Temp:** -20 to 60 °C (-4 to 140°F)
- **Approvals:** UL certified

www.replacementmonitors.com