

# Flat Panel Monitor

## MODEL T151KR



### RACKMOUNT – 15” DISPLAY



## Features

- High Brightness & Long Life TFT Panel
- Resolution (1024 x 768 pixels)
- Metal Cased Construction
- Mounting – Head or Desktop
- 12Vdc or 115/230Vac Power Inputs (Supplied with AC – 100-240Vac input)
- Touch screens - Easily integrated

## Specifications

- |                             |                                |                             |                                       |
|-----------------------------|--------------------------------|-----------------------------|---------------------------------------|
| • <b>Horizontal Scan</b>    | LEGACY 15-80KHz & VESA signals | • <b>Colors:</b>            | 16.2 M                                |
| • <b>Vertical Scan:</b>     | LEGACY 45-100Hz & VESA signals | • <b>Resolution:</b>        | 1024 x 768 pixels (native)            |
| • <b>AC Model:</b>          | 115/230V 50/60Hz               | • <b>Active Area:</b>       | 305 x 228 mm                          |
|                             | External AC/DC Power Pack      | • <b>Backlight Life:</b>    | 50,000 hours typical                  |
| • <b>Power Consumption:</b> | 50W (max)                      | • <b>Brightness:</b>        | 400 cd/m2 typical (nits)              |
| • <b>Dimensions:</b>        | 330 x 255 x 20 mm (approx)     | • <b>Contrast Ratio:</b>    | 700:1 (typical)                       |
| • <b>Weight:</b>            | 7 Kg (approx)                  | • <b>Viewing Angles:</b>    | 75/60/75/75                           |
| • <b>Housing:</b>           | RAL7032 Metal 19” Rack         | • <b>Response Time:</b>     | 8 msec (tr + tf) (typical)            |
| • <b>Operating Temp:</b>    | 0 to 50 °C (32 to 122°F)       | • <b>Input Connectors:</b>  | 15-pin HD, 15 pin LD (Schenck)        |
| • <b>Storage Temp:</b>      | -20 to 60 °C (-4 to 140°F)     | • <b>Sync. Type/Level:</b>  | Separate H&V (+/-ve) TTL              |
| • <b>Approvals:</b>         | Power Supply - UL + certified  | • <b>Video Connections:</b> | Analog RGB, (optional DVI, SVideo)    |
| • <b>Type:</b>              | A-Si Color TFT                 | • <b>Video Connections:</b> | TTL – 9 pin (optional), BNC Adaptable |

[www.replacementmonitors.com](http://www.replacementmonitors.com)